



# DURST SmartWasher Model DSW-128

The SmartWasher Fully Complies with Australian OH&S Regulations and is a patented non-hazardous, bioremediating parts cleaning system. The SmartWasher uses a warm aqueous degreasing solution called OzzyJuice. Both the SmartWasher and the OzzyJuice solutions have passed a number certifications and approvals. Overall, the SmartWasher reduces the release of VOC's, eliminates liquid hazardous waste and helps save our environment while protecting the health & wellbeing of your employees.



The largest and most versatile bioremediating parts washer available. This **SuperSink** model DSW-128 is IP65 Rated and packed with features. Large sink capacity with full **electronic controls with 2nd workstation**. Great for two users, large jobs, or lots of small parts.



### SmartWasher Certificates and Approvals



AQMD Certified  
DSW-SW3 Truck Grade OzzyJuice.  
DSW-SW6-8 Weapons Aviation Grade OzzyJuice.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act



Test Certificate in Compliance with the Device Safety Act  
National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice



Product Safety Certificate



DURST MOTOR & ELECTRIC INDUSTRIES P/L 189-189B ST JOHNS RD, GLEBE NSW 2037

Ph: 02 9660 1755 Fax: 02 9692 0251 Email: [sales@durst.com.au](mailto:sales@durst.com.au) Web: [www.durst.com.au](http://www.durst.com.au)

DWS-128 New Spec V1007.doc

# DURST SmartWasher Model DSW-128

## Specifications DWS-128

- Overall dimensions**  
L x W x H:
- 953mm x 1182mm x 1067mm
- Inside sink dimensions:**
- 661mm x 1042mm x 1178mm
- Shipping dimensions:**
- 978mm x 1207mm x 1182mm
- Material:**
- Blowmolded high density polyethylene for durability and consistent quality
- Pump capacity:**
- 93.75 W; 330 GPH at 1 foot; sump intake
- Electrical:**
- 240v, 50 Hz
- Heater:**
- 1000 watt industrial heater
- Weight:**
- 45 Kg empty
  - Holds 250 Kg. load
- Features:**
- ON/OFF control, side mounted
  - Supersink size for larger jobs or multiple operators
  - Flow timer with 10 and 30 minute increments
  - **Two** flow-through parts brush (allows 2 people to use the SmartWasher at the same time)
  - User regulated independent flow control from brush or nozzle.
  - Thermostat maintains fluid at 42°C (adjustable to 46°C)
  - Includes parts basket
  - Does not damage rubber or neoprene gaskets & seals
  - Warm cleaning solution
- Indicators:**
- Low fluid level indicator (red)
  - Standby/ready indicator (green)
  - Power indicator (green)
- Options Available :**
- Mobile trolley with wheel brakes
  - Peel able filters
  - Halogen light kit
- Filtration:**
- User changeable and disposable without hand tools or special equipment
  - Microbe impregnated
  - Filtration to 50 microns
- Cleaning solution:**
- Aqueous based surfactant cleaner
  - **NO** flashpoint
  - PH neutral, biodegradable
  - Non-toxic, no caustic, non-flammable, nonhazardous
  - **NO** VOCs, phosphates, formaldehyde, biocides or solvents
- Microbe treatment:**
- Environmental-shock resistant; preserved for minimum 18-month shelf life
  - Naturally occurring, non-pathogenic microbes



DURST MOTOR & ELECTRIC INDUSTRIES P/L 189-189B ST JOHNS RD, GLEBE NSW 2037

Ph: 02 9660 1755 Fax: 02 9692 0251 Email: [sales@durst.com.au](mailto:sales@durst.com.au) Web: [www.durst.com.au](http://www.durst.com.au)

DWS-128 New Spec V1007.doc